



**CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING & INVESTIGATIONS DIVISION  
BUILDING MATERIALS LISTING PROGRAM**

**LISTING SERVICE**

<b>LISTING No.:</b>	8180-2370:0001
<b>CATEGORY:</b>	8180 - NON-WOOD ROOF COVERING/ASSEMBLIES FOR WILDLAND URBAN INTERFACE (W.U.I)
<b>LISTEE:</b>	Liquiform Technologies Inc 9757 7th Street, Rancho Cucamonga, CA, 91730 Contact: Jones, Michael 951-285-5488 Email: michaeljones@weatherweld.com
<b>DESIGN:</b>	<p>Weatherweld Asphalt Emulsion a cold-applied protective coating that resists moisture intrusion and levels irregularities in roof surfaces.</p> <p>Refer to listee's data sheet for additional detailed product description and operational considerations.</p> <p>Class A:</p> <p>Deck: 15/32" AC Grade, Group 1 Exterior Plywood</p> <p>Incline: 5:12</p> <p>Underlayment: asphalt capsheet, single ply TPO, or modified bitumen</p> <p>Surfacing: Weatherweld Asphalt Emulsion with optional Acrylic or Aluminum coating</p> <p>Class A:</p> <p>Deck: 15/32" AC Grade, Group 1 Exterior Plywood</p> <p>Incline: 5:12</p>



**CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION**  
**OFFICE OF THE STATE FIRE MARSHAL**  
**FIRE ENGINEERING & INVESTIGATIONS DIVISION**  
**BUILDING MATERIALS LISTING PROGRAM**

**LISTING SERVICE**

	<p>Underlayment: asphalt capsheet</p> <p>Surfacing: Weatherweld Asphalt Emulsion with optional Acrylic or Aluminum coating</p> <p>Class A:</p> <p>Deck: 15/32" AC Grade, Group 1 Exterior Plywood</p> <p>Incline: 5:12</p> <p>Insulation: Carlisle InsulBase 1" or 2-1/2" polyisocyanurate</p> <p>Underlayment: GAF DensDeck</p> <p>Surfacing: Weatherweld Asphalt Emulsion with optional Acrylic or Aluminum coating</p>	
<b>RATING:</b>	Class A	
<b>INSTALLATION:</b>	In accordance with listee's printed installation instructions, applicable codes and ordinances, and in a manner acceptable to the authority having jurisdiction.	
<b>MARKING:</b>	Listee's Name, Model Number, Rating and ETL Label.	
<b>APPROVAL:</b>	Listed as Class A roof covering assembly as described under "Design" for use in the Wildland Urban Interface areas. Refer to listee's Installation Instruction Manual for details. Model complies with the applicable requirements in ASTM E108-20a.	
<b>NOTES:</b>		



**CALIFORNIA DEPARTMENT OF FORESTRY & FIRE PROTECTION  
OFFICE OF THE STATE FIRE MARSHAL  
FIRE ENGINEERING & INVESTIGATIONS DIVISION  
BUILDING MATERIALS LISTING PROGRAM**

**LISTING SERVICE**

4-5-23 DAL



This listing is based upon technical data submitted by the applicant. OSFM Fire Engineering staff has reviewed the test results and/or other data but does not make an independent verification of any claims. This listing is not an endorsement or recommendation of the item listed. This listing should not be used to verify correct operational requirements or installation criteria. Refer to listee's data sheet, installation instructions and/or other suitable information sources.

**Date Issued: 05/02/2023**

**Listing Expires: 06/30/2024**

Authorized By: **Victor Wong**, Program Coordinator  
Fire Engineering & Investigations Division