# **WEATHERWELD**

### **WW472049** Elastomeric Base Coat



WW472049 - WeatherWeld acrylic basecoat is a water-based, acrylic elastomeric coating designed to facilitate proper adhesion of WeatherWeld Title 24 compliant Cool Roof Coating to WeatherWeld emulsion. WW472049 provides superior protection against ponding water and eliminates the need for costly replacement.

PERFORMANCE		CERTIFICATIONS
PROPERTY	VALUE	
Appearance:	Liquid	( <sup>U</sup> L)
Color:	Buff	
Wet Adhesion – Asphalt Emulsion:	5.2 pli per ASTM D 6083	HANGAR
Solids (Volume / Weight):	54% / 67.7% per ASTM D 6083	
Viscosity:	110 ± 10 KU per ASTM D 6083	
Drying Time:	4-8 hours depending on temperature and humidity.	
		MORE INFO

#### Packaging:

1 Gallon Cans 5 Gallon Pails 55 Gallon Drums 250 Gallon Totes

> *WeatherWeld - A Division of Liquiform Technologies Inc.* 9757 7th St. #803 Rancho Cucamonga, CA 91730 | (888) 440-3224 | info@weatherweld.com

## **EATHER VELD** WWFG100 Elastomeric Base Coat

#### Coverage:

1.5 gallons per 100 square feet.

#### **Surface Preparation:**

Surface must be clean, dry and in good condition. Remove all debris, loose gravel, and dirt from the roof by brooming or vacuuming and power-wash the entire roof.

#### **Application**:

Apply WeatherWeld acrylic basecoat to finished WeatherWeld roof applications at a rate of 1.5 gallons

per 100 square feet.

#### Cleanup:

Clean wet coating from hands and tools with soap and water.

#### Warnings:

Use appropriate gloves and other protective clothing when handling this product. EMPLOYERS

should obtain a copy of the Material Safety Data Sheet (MSDS) from your supplier or directly from

WeatherWeld at the toll free number or website below.

#### Warranty:

Notwithstanding its usage as a component in a No Dollar Limit (NDL) guaranteed roof system, we, the manufacturer, warrant only that this product is free of defects for a period of twelve (12) months from date of original purchase. Many factors may affect the final results obtained from this product, including but not limited to: weather, workmanship, application equipment and prior condition of the application substrate. Proof of purchase is required.

DISCLAIMER OF WARRANTIES AND LIMITATION OF LIABILITY: THIS LIMITED WARRANTY IS IN LIEU OF ANY OTHER WARRANTIES EXPRESS OR IMPLIED INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FOR A PARTICULAR PURPOSE. MANUFACTURER SHALL HAVE NO LIABILITY OF ANY KIND BEYOND PRODUCT REPLACEMENT, INCLUDING FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES RESULTING FROM ANY DEFECTS OR ANY DELAYS CAUSED BY REPLACEMENT OR OTHERWISE. THIS LIMITED WARRANTY PROVIDES THE PURCHASER'S EXCLUSIVE REMEDY FOR ANY DEFECT IN THE PRODUCT.

Revised: 3/18/2024 WWTDS-001.pdf

## WeatherWeld - A Division of Liquiform Technologies Inc.

9757 7th St. #803 Rancho Cucamonga, CA 91730 | (888) 440-3224 | info@weatherweld.com | (888) 440-3224