



WW11111 Polyester Ply is a stitch bonded, high performance fabric for use in WeatherWeld roof encapsulation systems. The polyester ply is used in WeatherWeld Roofing Systems as the leveling layer for gravel roof systems. It is also designed as a separation sheet to bridge gaps between standing seam metal panels in WeatherWeld metal roof encapsulation systems.


PERFORMANCE

CERTIFICATIONS

PROPERTY	VALUE
Appearance:	Fabric
Color:	White to yellow white
Maximum VOC:	0 g/l
Maximum VOS:	0 lbs/gal
Elongation (Initial):	61-63 percent per ASTM D 1682
Tensile Strength Film (Initial):	57.1 lbs per ASTM D 1682
Trapezoidal Tear Strength:	16.1 lbs per ASTM D 1117
Mullen Burst:	176.8 lbs. per ASTM D 3786



MORE INFO



Packaging:

- 6 in. X 300 ft. Roll | 6 lbs (2.7 kg).
- 12 in. X 300 ft. Roll | 16 lbs (7.25 kg).
- 40 in. X 324 ft. Roll | 22 lbs (10.0 kg).
- 72 in. X 324 ft. Roll | 50 lbs (22.7 kg).
- 120 in. X 324 ft. Roll | 84 lbs (38.1 kg).

WeatherWeld - A Division of Liquiform Technologies Inc.

9757 7th St. #803 Rancho Cucamonga, CA 91730 | (888) 440-3224 | info@weatherweld.com

Coverage:

Coverage dependent on Roll size.

Surface Preparation:

Follow directions on the material being used with WW11111 Polyester Ply for proper preparation of the surface.

Application:

Gravel Surfaced Roofs: Embed one ply of polyester fabric into WeatherWeld asphalt emulsion. Application rates between 15 and 25 gallons per square depending on gravel size. insert language for 2" ply overlap. Extend polyester fabric 4" above base flashing termination.

Cleanup:

Clean up and properly dispose of all remenant polyester fabric in accordance with federal, state and local laws.

Warnings:

Product is combustible. Keep away from open flames. May cause mild skin irritation with prolonged exposure. Use protective measures to avoid contact with eyes and skin. Wash with soap and water after use. In case of eye contact, open eyelids wide and flush immediately with plenty of water for at least 15 minutes. In case of inhalation, remove the person from the contaminated area to fresh air. EMPLOYERS should obtain a copy of the Material Safety Data Sheet (MSDS) from your supplier or directly from WeatherWeld at the toll free number or website below.

Warranty:

Notwithstanding its usage as a component in a No Dollar Limit (NDL) guaranteed roof system, we, the manufacturer, warrant only that this product is free of defects for a period of twelve (12) months from date of original purchase. Many factors may affect the final results obtained from this product, including but not limited to: weather, workmanship, application equipment and prior condition of the application substrate. Proof of purchase is required.

DISCLAIMER OF WARRANTIES AND LIMITATION OF LIABILITY: THIS LIMITED WARRANTY IS IN LIEU OF ANY OTHER WARRANTIES EXPRESS OR IMPLIED INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FOR A PARTICULAR PURPOSE. MANUFACTURER SHALL HAVE NO LIABILITY OF ANY KIND BEYOND PRODUCT REPLACEMENT, INCLUDING FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES RESULTING FROM ANY DEFECTS OR ANY DELAYS CAUSED BY REPLACEMENT OR OTHERWISE. THIS LIMITED WARRANTY PROVIDES THE PURCHASER'S EXCLUSIVE REMEDY FOR ANY DEFECT IN THE PRODUCT.

WeatherWeld - A Division of Liquiform Technologies Inc.

9757 7th St. #803 Rancho Cucamonga, CA 91730 | (888) 440-3224 | info@weatherweld.com | (888) 440-3224